Infosafe No.: LQ5QA

ISSUED Date : 06/07/2021 ISSUED by: Prime

# **SAFETY DATA SHEET**

# LEAK LOCK

Section 1 - Identification

Product Identifier LEAK LOCK

**Company Name** Prime (ABN 93 142 654 564)

Address 1-3 Annick Crescent Laverton North Vic 3026 AUSTRALIA

**Telephone/Fax Number** Tel: +613 8348 9200 Fax: +613 8353 2083

Emergency Phone Number 1800 638 556 (24hrs)

Emergency Contact Name www.actrol.com.au

Recommended use of the chemical and restrictions on use

Thread sealant.

#### **Illicit Drug Precursors**

This product contains a Category III: Illicit Drug Reagent/Essential Chemical in the Code of Practice for Supply Division into Illicit Drug Manufacture.

# Section 2 - Hazard(s) Identification

#### GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Flammable liquids: Category 2

Eye damage/irritation: Category 2A

# Signal Word (s)

DANGER

#### Hazard Statement (s)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

# Pictogram (s)

Flame,Exclamation mark



#### **Precautionary Statement – Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

#### **Precautionary Statement – Response**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam (Alcohol resistant foam is preferred) to extinguish.

# Precautionary Statement – Storage

P403+P235 Store in a well-ventilated place. Keep cool.

# Precautionary Statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

#### **Other Information**

This product contains Ototoxic substances.

Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

# Section 3 - Composition and Information on Ingredients

# Ingredients

Name	CAS	Proportion
Ethanol	64- 17- 5	15- 40 %
Hydrated magnesium silicate	14807- 96- 6	15- 40 %
Isopropyl alchohol	67- 63- 0	1-5%
Ingredients determined not to be hazardous	Not required	Balance

# Section 4 - First Aid Measures

# Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

# Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

# Skin

Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.

# Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

#### First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

#### Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

# **Section 5 - Firefighting Measures**

#### Suitable Extinguishing Media

Carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

### Unsuitable Extinguishing Media

Do not use water jet.

#### Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

#### Specific hazards arising from the chemical

Highly flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

#### •3YE

Decomposition Temperature Not available

#### Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

# Section 6 - Accidental Release Measures

#### **Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

# Section 7 - Handling and Storage

#### **Precautions for Safe Handling**

Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

#### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions

comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

#### **Section 8 - Exposure Controls and Personal Protection**

#### Occupational exposure limit values

No exposure value assigned for this material. However, the available exposure limits for ingredients are listed below:

Ethanol TWA: 1000 ppm TWA: 1880 mg/m<sup>3</sup> Isopropyl alcohol TWA: 400 ppm, 983 mg/m<sup>3</sup> STEL: 500 ppm, 1230 mg/m<sup>3</sup> Magnesium silicate talc TWA: 2.5 mg/m<sup>3</sup> TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a fiveday week. STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eighthour workday. Source: Safe Work Australia

# **Biological Monitoring**

Name: Isopropanol Determinant: Acetone in urine Value: 40 mg/l Sampling time: End of shift at end of workweek Source: American Conference of Industrial Hygienists (ACGIH) **Control Banding** 

Not available

#### **Engineering Controls**

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

#### **Respiratory Protection**

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable mist/dust filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

#### Eye and Face Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

#### **Hand Protection**

Wear gloves of impervious material such as nitrile rubber. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

# Thermal Hazards

No further relevant information available.

### **Body Protection**

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

#### Section 9 - Physical and Chemical Properties

Properties	Description	Properties	Description
Form	Liquid	Appearance	Blue flowable paste with slight odour.
Colour	Blue	Odour	Slight odour
Melting Point	Not available	Boiling Point	78 °C
Decomposition Temperature	Not available	Solubility in Water	Appreciable
Specific Gravity	1.3 (20 °C)	рН	Not applicable
Vapour Pressure	44 mmHg (20 °C)	Relative Vapour Density (Air=1)	>1
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Partition Coefficient: n-octanol/water (log value)	Not available
Flash Point	15.6 °C	Flammability	Highly flammable liquid
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	3.3%
Flammable Limits - Upper	19.0%	Explosion Properties	Not available
Oxidising Properties	Not available		

#### Section 10 - Stability and Reactivity

Reactivity

Reacts with incompatible materials.

### Chemical Stability

Stable under normal conditions of storage and handling.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to Avoid

Heat, open flames and other sources of ignition.

**Incompatible Materials** Strong oxidising agents.

# Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: oxides of nitrogen, carbon dioxide and carbon monoxide.

Hazardous Polymerization

Not available

# Section 11 - Toxicological Information

# **Toxicology Information**

No toxicity data available for this material.

# Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

# Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

May be irritating to skin. The symptoms may include redness, itching and swelling.

#### Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

#### **Respiratory Sensitisation**

Not expected to be a respiratory sensitiser.

Skin Sensitisation Not expected to be a skin sensitiser.

Germ Cell Mutagenicity Not considered to be a mutagenic hazard.

#### Carcinogenicity

Not considered to be a carcinogenic hazard.

Isopropyl alcohol is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC). Magnesium silicate talc is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

#### Reproductive Toxicity

Not considered to be toxic to reproduction.

#### STOT - Single Exposure

Not expected to cause toxicity to a specific target organ.

# STOT - Repeated Exposure

Not expected to cause toxicity to a specific target organ.

#### Aspiration Hazard

Not expected to be an aspiration hazard.

#### **Other Information**

This product contains Ototoxic substances.

Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

### Section 12 - Ecological Information

#### Ecotoxicity

No ecological data available for this material.
Persistence and degradability
Not available
Mobility
Not available
Bioaccumulative Potential
Not available
Other Adverse Effects
Not available
Environmental Protection
Do not discharge this material into waterways, drains and sewers.
Hazardous to the Ozone Layer
This product is not expected to deplete the ozone layer.

Section 13 - Disposal Considerations

# Disposal Considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain flammable residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Advise flammable nature.

To minimise personal exposure to the chemical, refer to Section 8-Exposure controls and personal protection.

# Section 14 - Transport Information

# Transport Information

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Class 3 - Flammable Liquids are incompatible in a placard load with any of the following: Class 1: Explosives - Division 2.1: Flammable Gases. (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L) - Division 2.3: Toxic Gases - Division 4.2: Spontaneously Combustible Substances - Division 5.1: Oxidising substances - Division 5.2: Organic Peroxides - Class 6: Toxic or Infectious Substances (where the flammable liquid is nitromethane) - Class 7: Radioactive materials unless specifically exempted. Marine Transport (IMO/IMDG): Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. Class/Division: 3 UN No: 1993 Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (Contains Ethanol, Isopropyl alcohol) Packing Group: II EMS: F-E, S-E Special Provisions: 274 Air Transport (ICAO/IATA): Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. Class/Division: 3 UN No: 1993 Proper Shipping Name: flammable liquid, n.o.s. (Contains Ethanol, Isopropyl alcohol) Packing Group: II Packaging Instructions (passenger & cargo): 353 Packaging Instructions (cargo only): 364 Hazard Label: Flammable Liquid Special Provisions: A3 ADG U.N. Number 1993 **ADG Proper Shipping Name** FLAMMABLE LIQUID, N.O.S.(Contains Ethanol, Isopropyl alcohol) ADG Transport Hazard Class 3 **ADG Packing Group** П Hazchem Code •3YE **IERG Number** 14 **Special Precautions for User** Not available IMDG Marine pollutant No **Transport in Bulk** Not available Section 15 - Regulatory Information

#### **Regulatory Information**

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia. Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). Poisons Schedule Not Scheduled Australia (AICS/AIIC) All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS). Montreal Protocol Not listed Stockholm Convention Not available **Rotterdam Convention** Not available International Convention for the Prevention of Pollution from Ships (MARPOL) Not available Agricultural and Veterinary Chemicals Act 1994 Not available **Basel Convention** Not available

# Section 16 - Any Other Relevant Information

#### **Date of Preparation**

SDS Reviewed: July 2021 Supersedes: June 2016

# Version Number

Version 2.0

# Literature References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice. Standard for the Uniform Scheduling of Medicines and Poisons. Australian Code for the Transport of Dangerous Goods by Road & Rail. Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals. Code of Practice for Supply Diversion into Illicit Drug Manufacture. National Code of Practice for Chemicals of Security Concern. Agricultural Compounds and Veterinary Chemicals Act. International Agency for Research on Cancer (IARC) Monographs. Montreal Protocol on Substances that Deplete the Ozone Layer. Stockholm Convention on Persistent Organic Pollutants (POPs). Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade. Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal. International Air Transport Association (IATA) Dangerous Goods Regulations. International Maritime Dangerous Goods (IMDG) Code. Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals.

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

#### **END OF SDS**

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd. Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd. The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.