



## Safety Data Sheet

LOCTITE 567 TB250ML EN/CH/JP

Page 1 of 8

SDS No. : 546886

V001.1

Date of issue: 19.05.2021

### Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** LOCTITE 567 TB250ML EN/CH/JP

**Intended use:** Adhesive/Sealant

**Supplier:**

Henkel Australia Pty Ltd  
135-141 Canterbury Road  
Kilsyth, Victoria, 3137  
Australia

Phone: +61 (3) 9724 6444

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

### Section 2. Hazards identification

**Classification of the substance or mixture**

Hazardous according to the criteria of Safe Work Australia.

**GHS Classification:**

**Hazard Class**

Skin irritation  
Serious eye irritation  
Skin sensitizer  
Target Organ Systemic Toxicant -  
Single exposure  
Acute hazards to the aquatic  
environment  
Chronic hazards to the aquatic  
environment

**Hazard Category**

Category 2  
Category 2A  
Category 1  
Category 3  
Category 2  
Category 2

**Target organ**

respiratory tract irritation

**Hazard pictogram:**



**Signal word:**

Warning

<b>Hazard statement(s):</b>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H411 Toxic to aquatic life with long lasting effects.
<b>Precautionary Statement(s):</b>	
<b>Prevention:</b>	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362 Take off contaminated clothing. P391 Collect spillage.
<b>Storage:</b>	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
<b>Disposal:</b>	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

**Dangerous Goods information:**

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Exempt under Special Provision AU01 : Environmentally Hazardous Substances meeting the descriptions of UN3077 or UN3082 are not subject to this Code when transported by road or rail in;

- a) Packagings that do not incorporate a receptacle exceeding 500 kg (L); or
- b) Intermediate Bulk Containers.

**Section 3. Composition / information on ingredients**

**General chemical description:** Mixture  
**Type of preparation:** Anaerobic Sealant

**Identity of ingredients:**

Chemical ingredients	CAS-No.	Proportion
3,3,5 Trimethylcyclohexyl methacrylate	7779-31-9	10- 30 %
Propane-1,2-diol	57-55-6	< 3 %
non hazardous ingredients~		60- 100 %

**Section 4. First aid measures**

**Ingestion:** Rinse mouth, do not induce vomiting, consult a doctor.

**Skin:** Rinse with running water and soap.  
Seek medical advice.

**Eyes:** Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

**Inhalation:** Move to fresh air. If symptoms persist, seek medical advice.

<b>First Aid facilities:</b>	Eye wash Normal washroom facilities
<b>Medical attention and special treatment:</b>	Treat symptomatically and supportively.

### Section 5. Fire fighting measures

<b>Suitable extinguishing media:</b>	Foam, extinguishing powder, carbon dioxide. Water spray or fog.
<b>Improper extinguishing media:</b>	High pressure waterjet
<b>Decomposition products in case of fire:</b>	Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide Carbon dioxide.
<b>Special protective equipment for fire-fighters:</b>	Wear full protective clothing. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).
<b>Additional fire fighting advice:</b>	In case of fire, keep containers cool with water spray.

### Section 6. Accidental release measures

<b>Personal precautions:</b>	Avoid skin and eye contact. Ensure adequate ventilation.
<b>Environmental precautions:</b>	Do not let product enter drains.
<b>Clean-up methods:</b>	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

### Section 7. Handling and storage

<b>Precautions for safe handling:</b>	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.
<b>Conditions for safe storage:</b>	Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

### Section 8. Exposure controls / personal protection

#### National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
PROPANE-1,2-DIOL TOTAL: (VAPOUR & PARTICULATES) 57-55-6	Total vapour and particulates.	150	474	-	-	-	-
PROPANE-1,2-DIOL: PARTICULATES ONLY 57-55-6	Particulate.		10	-	-	-	-

<b>Engineering controls:</b>	Ensure good ventilation/suction at the workplace.
<b>Eye protection:</b>	Safety goggles or safety glasses with side shields.
<b>Skin protection:</b>	Use impermeable gloves and protective clothing as necessary to prevent skin contact.  Neoprene gloves.  Butyl rubber gloves.  Natural rubber gloves.
<b>Respiratory protection:</b>	If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

## Section 9. Physical and chemical properties

<b>Appearance:</b>	Off white solid
<b>Odor:</b>	mild
<b>pH:</b>	Not available.
<b>Specific gravity:</b>	1.15
<b>Boiling point:</b>	> 149 °C (> 300.2 °F)
<b>Flash point:</b>	> 93 °C (> 199.4 °F)
<b>Density:</b>	1.15 g/cm <sup>3</sup>
<b>Solubility in water:</b>	Insoluble
<b>VOC content:</b> (2010/75/EC)	< 3 %

## Section 10. Stability and reactivity

<b>Stability:</b>	Stable under recommended storage conditions.
<b>Conditions to avoid:</b>	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.
<b>Incompatible materials:</b>	Reacts with strong oxidants.
<b>Hazardous decomposition products:</b>	Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.  Toxic fluorine compounds. Ketones.

## Section 11. Toxicological information

**Health Effects:****Ingestion:****Skin:**

Ingestion may cause stomach ache and vomiting.

Irritating to skin.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause skin sensitization.

**Eyes:**

Causes serious eye irritation.

**Inhalation:**

Symptoms may include severe irritation, pain, tearing, blurred vision.

This product is irritating to the respiratory system.

**Aggravated med.  
condition:**

Eye, skin, and respiratory disorders.

**Acute toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD0 LD50 LD0 LD50	> 5,000 mg/kg > 5,000 mg/kg > 2,000 mg/kg > 2,000 mg/kg	oral oral  dermal dermal		rat rat rat rat	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Propane-1,2-diol 57-55-6	LD50 LC50 LD50	22,000 mg/kg > 317.042 mg/l > 2,000 mg/kg	oral inhalation dermal	2 h	rat rabbit rabbit	not specified not specified not specified

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Propane-1,2-diol 57-55-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Propane-1,2-diol 57-55-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Propane-1,2-diol 57-55-6	not sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propane-1,2-diol 57-55-6	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	without with and without		Ames Test OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane-1,2-diol 57-55-6	negative negative negative	oral: gavage intraperitoneal oral: gavage		rat mouse rat	not specified not specified not specified

**Repeated dose toxicity:**

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	NOAEL=1,000 mg/kg	oral: gavage	28 ddaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane-1,2-diol 57-55-6	NOAEL=1,700 mg/kg	oral: feed	2 yearsdaily	rat	not specified
Propane-1,2-diol 57-55-6	NOAEL=1000 mg/m3	inhalation	90 d6 h/d, 5 d/w	rat	not specified

**Section 12. Ecological information****General ecological information:**

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards., Do not empty into drains / surface water / ground water.

**Ecotoxicity:**

Harmful to aquatic life with long lasting effects.

**Toxicity:**

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LC50	1.9 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	EC50	14.43 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	EC10	0.43 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propane-1,2-diol 57-55-6	LC50	> 10,000 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Propane-1,2-diol 57-55-6	EC50	18,340 mg/l	Daphnia	48 h	Ceriodaphnia dubia	other guideline:
Propane-1,2-diol 57-55-6	EC50	24,200 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propane-1,2-diol 57-55-6	NOEC	15,000 mg/l	Algae	14 d	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propane-1,2-diol 57-55-6	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

**Persistence and degradability:**

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	not readily biodegradable.	aerobic	16.8 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Propane-1,2-diol 57-55-6	not inherently biodegradable	aerobic	60 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Propane-1,2-diol 57-55-6	readily biodegradable	aerobic	> 81.7 - 100 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

**Bioaccumulative potential / Mobility in soil:**

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	5.25				20 °C	OECD Guideline 117 (Partition Coefficient (n- octanol / water), HPLC Method)
Propane-1,2-diol 57-55-6	-1.07				20.5 °C	EU Method A.8 (Partition Coefficient)

**Section 13. Disposal considerations****Waste disposal of product:**

Dispose of in accordance with local and national regulations.

**Disposal for uncleaned package:**

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.  
Disposal must be made according to official regulations.

**Section 14. Transport information****Road and Rail Transport:**

## Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).  
Exempt under Special Provision AU01 : Environmentally Hazardous Substances meeting the descriptions of UN3077 or UN3082 are not subject to this Code when transported by road or rail in;  
a) Packagings that do not incorporate a receptacle exceeding 500 kg (L); or  
b) Intermediate Bulk Containers.

**Marine transport IMDG:**

UN no.: 3082  
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S. (3,3,5-Trimethylcyclohexyl methacrylate, 1,4-Naphthoquinone)  
Class or division: 9  
Packing group: III  
EmS: F-A ,S-F  
Seawater pollutant: Marine pollutant

**Marine transport IMDG:**

Not available.

**Air transport IATA:**

UN no.:	3082
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (3,3,5-Trimethylcyclohexyl methacrylate,1,4-Naphthoquinone)
Class or division:	9
Packing group:	III
Packing instructions (passenger)	964
Packing instructions (cargo)	964

**Further information for transport:**

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

**Section 15. Regulatory information****SUSMP Poisons Schedule**

None

**Section 16. Other information****Abbreviations/acronyms:**

IMDG: International Maritime Dangerous Goods code  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
GHS: Globally Harmonized System  
AIIC - Australian Inventory of Industrial Chemicals (AIIC)  
AICIS - Australian Industrial Chemicals Introduction Scheme

**Reason for issue:**

Reviewed SDS. Reissued with new date. involved chapters: 2,9,11,14,16

**Date of previous issue:**

14.10.2016

**Disclaimer:**

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.